

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

XSF SILVER X-101

Date of compilation: 25/09/2019 Revised: 18/07/2022 Version: 2 (Replaced 1)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: XSF SILVER X-101

Other means of identification:

UFI: 5M00-Q0M9-7001-FY6E

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Paints and varnishes. For professional users only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Spray One Europe GmbH

Im Ginselt 5

D-66709 Weiskirchen - Germany Phone: Tel.: +49 (0)162 20 500 97

msds@spray-one.com

1.4 Emergency telephone number: +49 (0)551-19240 (Giftinformationszentrum-Nord)

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Flam. Lig. 3: Flammable liquids, Category 3, H226

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Warning





Hazard statements:

H226 - Flammable liquid and vapour.

H336 - May cause drowsiness or dizziness.

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P235: Keep cool.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking.

Substances that contribute to the classification

2-methoxy-1-methylethyl acetate; N-butyl acetate

UFI: 5M00-Q0M9-7001-FY6E

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

Endocrine-disrupting properties: The product fails to meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

XSF SILVER X-101

Date of compilation: 25/09/2019 Revised: 18/07/2022 Version: 2 (Replaced 1)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of chemical products

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification		Concentration
CAS:	108-65-6	2-methoxy-1-methyl	ethyl acetate ⁽¹⁾	ATP ATP01	
EC: Index: REACH:	203-603-9 607-195-00-7 01-2119475791-29- XXXX	Regulation 1272/2008	Flam. Liq. 3: H226 - Warning		45 - <55 %
CAS:	108-65-6	2-methoxy-1-methylethyl acetate ⁽²⁾		Self-classified	
EC: Index: REACH:	203-603-9 607-195-00-7 01-2119475791-29- XXXX	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336 - Warning		25 - <50 %
CAS:	123-86-4	N-butyl acetate(2)		ATP CLP00	
EC: Index: REACH:	204-658-1 607-025-00-1 01-2119485493-29- XXXX	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning		40 - <50 %
CAS:	67-64-1	acetone(1)		ATP CLP00	
EC: Index: REACH:	200-662-2 606-001-00-8 01-2119471330-49- XXXX	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger		<0,5 %
CAS:	70657-70-4	2-methoxypropyl ace	etate ⁽²⁾	ATP CLP00	
EC: Index: REACH:	274-724-2 607-251-00-0 Non-applicable	Regulation 1272/2008	Flam. Liq. 3: H226; Repr. 1B: H360D; STOT SE 3: H335 - Danger		<0,2 %

⁽¹⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

In case of consumption, seek immediate medical assistance showing the SDS for the product.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

⁽²⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

XSF SILVER X-101

Date of compilation: 25/09/2019 Revised: 18/07/2022 Version: 2 (Replaced 1)

SECTION 4: FIRST AID MEASURES (continued)

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

XSF SILVER X-101

Date of compilation: 25/09/2019 Revised: 18/07/2022 Version: 2 (Replaced 1)

SECTION 7: HANDLING AND STORAGE (continued)

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 25 °C

Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:


Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occu	Occupational exposure limits		
2-methoxy-1-methylethyl acetate	IOELV (8h)	50 ppm	275 mg/m ³	
CAS: 108-65-6 EC: 203-603-9	IOELV (STEL)	100 ppm	550 mg/m ³	
N-butyl acetate	IOELV (8h)	50 ppm	241 mg/m ³	
CAS: 123-86-4	IOELV (STEL)	150 ppm	723 mg/m ³	
2-methoxy-1-methylethyl acetate	IOELV (8h)	50 ppm	275 mg/m ³	
CAS: 108-65-6 EC: 203-603-9	IOELV (STEL)	100 ppm	550 mg/m ³	
acetone	IOELV (8h)	500 ppm	1210 mg/m ³	
CAS: 67-64-1 EC: 200-662-2	IOELV (STEL)			

DNEL (Workers):

		Short e	xposure	Long e	xposure
Identification	Systemic	Local	Systemic	Local	
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	796 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	550 mg/m ³	275 mg/m ³	Non-applicable
N-butyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-86-4	Dermal	11 mg/kg	Non-applicable	11 mg/kg	Non-applicable
EC: 204-658-1	Inhalation	600 mg/m ³	600 mg/m ³	300 mg/m ³	300 mg/m ³
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	796 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	550 mg/m ³	275 mg/m ³	Non-applicable





This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

XSF SILVER X-101

Date of compilation: 25/09/2019 Revised: 18/07/2022 Version: 2 (Replaced 1)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short e	Short exposure		xposure
Identification		Systemic	Local	Systemic	Local
acetone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 67-64-1	Dermal	Non-applicable	Non-applicable	186 mg/kg	Non-applicable
EC: 200-662-2	Inhalation	Non-applicable	2420 mg/m ³	1210 mg/m ³	Non-applicable

DNEL (General population):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	33 mg/m ³	33 mg/m ³
N-butyl acetate	Oral	2 mg/kg	Non-applicable	2 mg/kg	Non-applicable
CAS: 123-86-4	Dermal	6 mg/kg	Non-applicable	6 mg/kg	Non-applicable
EC: 204-658-1	Inhalation	300 mg/m ³	300 mg/m ³	35,7 mg/m ³	35,7 mg/m ³
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	33 mg/m ³	33 mg/m ³
acetone	Oral	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
CAS: 67-64-1	Dermal	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
EC: 200-662-2	Inhalation	Non-applicable	Non-applicable	200 mg/m ³	Non-applicable

PNEC:

Identification				
2-methoxy-1-methylethyl acetate	STP	100 mg/L	Fresh water	0,635 mg/L
CAS: 108-65-6	Soil	0,29 mg/kg	Marine water	0,064 mg/L
EC: 203-603-9	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg
N-butyl acetate	STP	35,6 mg/L	Fresh water	0,18 mg/L
CAS: 123-86-4	Soil	0,09 mg/kg	Marine water	0,018 mg/L
EC: 204-658-1	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,098 mg/kg
2-methoxy-1-methylethyl acetate	STP	100 mg/L	Fresh water	0,635 mg/L
CAS: 108-65-6	Soil	0,29 mg/kg	Marine water	0,064 mg/L
EC: 203-603-9	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg
acetone	STP	100 mg/L	Fresh water	10,6 mg/L
CAS: 67-64-1	Soil	29,5 mg/kg	Marine water	1,06 mg/L
EC: 200-662-2	Intermittent	21 mg/L	Sediment (Fresh water)	30,4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	3,04 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.





This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

XSF SILVER X-101

Date of compilation: 25/09/2019 Revised: 18/07/2022 Version: 2 (Replaced 1)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves	CAT III	EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN ISO 21420:2020	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield	CATII	EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	CAT III	EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
+	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	- ∰	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Odour:

Odour threshold:

Liquid

Fluid

Fluid

Characteristic

Non-applicable *

Volatility:

Boiling point at atmospheric pressure: 135 °C Vapour pressure at 20 °C: 1009 Pa

*Not relevant due to the nature of the product, not providing information property of its hazards.



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

XSF SILVER X-101

Date of compilation: 25/09/2019 Revised: 18/07/2022 Version: 2 (Replaced 1)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Vapour pressure at 50 °C: 4875,82 Pa (4,88 kPa) Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: 928 kg/m³
Relative density at 20 °C: 0,928

Dynamic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 40 °C: Non-applicable * Concentration: Non-applicable * pH: Non-applicable * Vapour density at 20 °C: Non-applicable * Partition coefficient n-octanol/water 20 °C: Non-applicable * Solubility in water at 20 °C: Non-applicable * Solubility properties: Non-applicable * Decomposition temperature: Non-applicable * Melting point/freezing point: Non-applicable *

Flammability:

Flash Point: 34 °C

Flammability (solid, gas): Non-applicable *

Autoignition temperature: 315 °C

Lower flammability limit: Not available

Upper flammability limit: Not available

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:

Oxidising properties:

Non-applicable *

Corrosive to metals:

Heat of combustion:

Aerosols-total percentage (by mass) of flammable components:

Non-applicable *

Non-applicable *

Other safety characteristics:

Surface tension at 20 °C:

Refraction index:

Non-applicable *

Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

XSF SILVER X-101

Date of compilation: 25/09/2019 Revised: 18/07/2022 Version: 2 (Replaced 1)

SECTION 10: STABILITY AND REACTIVITY (continued)

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

IARC: Non-applicable

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

XSF SILVER X-101

Date of compilation: 25/09/2019 Revised: 18/07/2022 Version: 2 (Replaced 1)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
N-butyl acetate	LD50 oral	12789 mg/kg	Rat
CAS: 123-86-4	LD50 dermal	14112 mg/kg	Rabbit
EC: 204-658-1	LC50 inhalation	23,4 mg/L (4 h)	Rat
2-methoxy-1-methylethyl acetate	LD50 oral	8532 mg/kg	Rat
CAS: 108-65-6	LD50 dermal	>5000 mg/kg	Rat
EC: 203-603-9	LC50 inhalation	30 mg/L (4 h)	Rat
2-methoxy-1-methylethyl acetate	LD50 oral	8532 mg/kg	Rat
CAS: 108-65-6	LD50 dermal	5100 mg/kg	Rat
EC: 203-603-9	LC50 inhalation	30 mg/L (4 h)	Rat
acetone	LD50 oral	5800 mg/kg	Rat
CAS: 67-64-1	LD50 dermal	7426 mg/kg	Rabbit
EC: 200-662-2	LC50 inhalation	76 mg/L (4 h)	Rat

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus	
2-methoxy-1-methylethyl acetate	LC50	161 mg/L (96 h)	Pimephales promelas	Fish	
CAS: 108-65-6	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean	
EC: 203-603-9	EC50	Non-applicable			
N-butyl acetate	LC50	Non-applicable			
CAS: 123-86-4	EC50	Non-applicable			
EC: 204-658-1	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae	
2-methoxy-1-methylethyl acetate	LC50	161 mg/L (96 h)	Pimephales promelas	Fish	
CAS: 108-65-6	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean	
EC: 203-603-9	EC50	Non-applicable			
acetone	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish	
CAS: 67-64-1	EC50	8800 mg/L (48 h)	Daphnia pulex	Crustacean	
EC: 200-662-2	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae	

Chronic toxicity:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

XSF SILVER X-101

Date of compilation: 25/09/2019 Revised: 18/07/2022 Version: 2 (Replaced 1)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification		Concentration	Species	Genus
2-methoxy-1-methylethyl acetate	NOEC	47,5 mg/L	Oryzias latipes	Fish
CAS: 108-65-6 EC: 203-603-9	NOEC	100 mg/L	Daphnia magna	Crustacean
N-butyl acetate	NOEC	Non-applicable		
CAS: 123-86-4 EC: 204-658-1	NOEC	23,2 mg/L	Daphnia magna	Crustacean
2-methoxy-1-methylethyl acetate	NOEC	47,5 mg/L	Oryzias latipes	Fish
CAS: 108-65-6 EC: 203-603-9	NOEC	100 mg/L	Daphnia magna	Crustacean
acetone	NOEC	Non-applicable		
CAS: 67-64-1 EC: 200-662-2	NOEC	2212 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradab	ility
2-methoxy-1-methylethyl acetate	BOD5	Non-applicable	Concentration	785 mg/L
CAS: 108-65-6	COD	Non-applicable	Period	8 days
EC: 203-603-9	BOD5/COD	Non-applicable	% Biodegradable	100 %
N-butyl acetate	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 123-86-4	COD	Non-applicable	Period	5 days
EC: 204-658-1	BOD5/COD	Non-applicable	% Biodegradable	84 %
2-methoxy-1-methylethyl acetate	BOD5	Non-applicable	Concentration	785 mg/L
CAS: 108-65-6	COD	Non-applicable	Period	8 days
EC: 203-603-9	BOD5/COD	Non-applicable	% Biodegradable	100 %
acetone	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 67-64-1	COD	Non-applicable	Period	28 days
EC: 200-662-2	BOD5/COD	Non-applicable	% Biodegradable	96 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bio	Bioaccumulation potential		
2-methoxy-1-methylethyl acetate	BCF	1		
CAS: 108-65-6	Pow Log	0.43		
EC: 203-603-9	Potential	Low		
N-butyl acetate	BCF	4		
CAS: 123-86-4	Pow Log	1.78		
EC: 204-658-1	Potential	Low		
2-methoxy-1-methylethyl acetate	BCF	1		
CAS: 108-65-6	Pow Log	0.43		
EC: 203-603-9	Potential	Low		
acetone	BCF	1		
CAS: 67-64-1	Pow Log	-0.24		
EC: 200-662-2	Potential	Low		

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
N-butyl acetate	Koc	Non-applicable	Henry	Non-applicable
CAS: 123-86-4	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 204-658-1	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Non-applicable
acetone	Koc	1	Henry	2,93 Pa·m³/mol
CAS: 67-64-1	Conclusion	Very High	Dry soil	Yes
EC: 200-662-2	Surface tension	2,304E-2 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:





This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

XSF SILVER X-101

Date of compilation: 25/09/2019 Revised: 18/07/2022 Version: 2 (Replaced 1)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



14.1 UN number or ID number: UN1263 14.2 UN proper shipping name: PAINT 14.3 Transport hazard class(es): 3 3 Labels: III

14.4 Packing group: 14.5 Environmental hazards: No 14.6 Special precautions for user

> Special regulations: 163, 367, 650

> Tunnel restriction code:

Physico-Chemical properties:

see section 9

Limited quantities: 5 L

14.7 Maritime transport in bulk according to IMO

instruments:

Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 40-20:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

XSF SILVER X-101

No

Date of compilation: 25/09/2019 Revised: 18/07/2022 Version: 2 (Replaced 1)

SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number or ID number: UN1263
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 3

Labels: 3 **14.4 Packing group:** III

14.5 Marine pollutant:14.6 Special precautions for user

Special regulations: 223, 955, 163, 367

EmS Codes: F-E, S-E Physico-Chemical properties: see section 9

Limited quantities: 5 L

Segregation group: Non-applicable

14.7 Maritime transport in bulk according to IMO

Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:

SECTION 15: REGULATORY INFORMATION



14.1 UN number or ID number: UN1263
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 3
Labels: 3

14.4 Packing group: III

14.4 Packing group: III
14.5 Environmental hazards: No
14.6 Special precautions for user

Physico-Chemical properties:

14.7 Maritime transport in bulk according to IMO

instruments:

instruments:

see section 9 Non-applicable

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors: Contains acetone. Product under the provisions of Article 9. However, products that contain explosives precursors only to such a small extent and in such complex mixtures that the extraction of the explosives precursors is technically extremely difficult should be excluded from the scope of this Regulation. Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

XSF SILVER X-101

Date of compilation: 25/09/2019 Revised: 18/07/2022 Version: 2 (Replaced 1)

SECTION 15: REGULATORY INFORMATION (continued)

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H336: May cause drowsiness or dizziness.

H226: Flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Repr. 1B: H360D - May damage the unborn child.

STOT SE 3: H335 - May cause respiratory irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

STOT SE 3: Calculation method

Flam. Liq. 3: Calculation method (2.6.4.3)

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu

http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.